



AUTOTIG 18








CODE	←	→	H
ST4401-00	4 m	12.5'	
ST4801-00	8 m	25'	M12x1

TECHNICAL DATA			
	AUTOTIG 18		
<u>≠</u>	0.90 Kg	1.98 lb	
V PEAK	113		
À	Argon		
Ø = -	0,5÷4,0 mm	.020"÷5/32"	
X 100%	320A DC - 270A AC		
₩	4 bar		
≱ ‡	1.5	/min	











TIG CONSUMABLE KITS

STARTER KITS



9 - 20 - 20 HC - 25

CODE	Ø		
TT0221	1,6 mm	1/16"	1
TT0222	2,4 mm	3/32"	1

17 - 18 - 18 HC - 26

CODE	Ø		
TT0223	1,6 mm	1/16"	1
TT0224	2,4 mm	3/32"	1

24 - 24W

CODE	Ø		
TT0226	1,6 mm	1/16"	1

STARTER KITS



9 - 20 - 20 HC - 25

CODE	Ø			
TT0101	1,6 mm	1/16"	WR2	1
TT0102	2,4 mm	3/32"	WR2	1

17 - 18 - 18 HC - 26

CODE	Q	Ď		
TT0103	1,6 mm	1/16"	WR2	1
TT0104	2,4 mm	3/32"	WR2	1
TT0105	3,2 mm	1/8"	WR2	1

24 - 24W

CODE	Ø			
TT0203	1,6 mm	1/16"	WC20	1
TT0204	2,4 mm	3/32"	WC20	1



TIG CONSUMABLE KITS

STARTER KITS WITH BACK CAP



9 - 20 - 20 HC - 25

CODE	Q	Ď		
TT0021	1,6 mm	1/16"	WC20	1
TT0022	2,4 mm	3/32"	WC20	1

17 - 18 - 18 HC - 26

CODE	Ø			
TT0023	1,6 mm	1/16"	WC20	1
TT0024	2,4 mm	3/32"	WC20	1
TT0025	3,2 mm	1/8"	WC20	1

MASTER KITS



9 - 20 - 20 HC - 25


CODE	Ø	(
TT0109	1,0 mm - 1,6 mm - 2,0 mm - 2,4 mm - 3,2 mm	1

17 - 18 - 18 HC - 26

CODE	Ø		
TT0110	1,6 mm - 2,0 mm - 2,4 mm - 3,2 mm - 4,0 mm	1	l



TIG 17 / 18 / 18 HC / 26 - CONSUMABLES



STANDARD

	CODE	Gr	Q)	\longleftrightarrow	REF	
1	TC0002	4	6,4 mm	1/4"	47 mm	10N50	10
1	TC0003	5	8 mm	5/16"	47 mm	10N49	10
1	TC0004	6	9,8 mm	3/8"	47 mm	10N48	10
1	TC0005	7	11,2 mm	7/16"	47 mm	10N47	10
1	TC0006	 8	12,7 mm	1/2"	47 mm	10N46	10
1	TC0007	10	15,7 mm	5/8"	47 mm	10N45	10
1	TC0008	12	19 mm	3/4"	47 mm	10N44	10
1	TC0091	5	8 mm	5/16"	76 mm	10N49L	10
1	TC0092	6	9,5 mm	3/8"	76 mm	10N48L	10
1	TC0093	7	11 mm		76 mm	10N47L	10
2	TE0001-05		0,5 mm	.020"	47 mm	10N29	10
2	TE0001-10		1,0 mm	.040"	47 mm	10N30	10
2	TE0001-16		1,6 mm	1/16"	47 mm	10N31	10
2	TE0001-20		2,0 mm	5/64"	47 mm	-	10
2	TE0001-24		2,4 mm	3/32"	47 mm	10N32	10
2	TE0001-32		3,2 mm	1/8"	47 mm	10N28	10
2	TE0001-40		4,0 mm	5/32"	47 mm	406488	10
2	TE0001-48		4,8 mm	3/16"	47 mm	30126	10

	CODE		Gr	Ø		\leftarrow	REF	
3	TD0001-05			0,5 mm	.020"	50 mm	10N21	10
3	TD0001-10			1,0 mm	.040"	50 mm	10N22	10
3	TD0001-16			1,6 mm	1/16"	50 mm	10N23	10
3	TD0001-20			2,0 mm	5/64"	50 mm	-	10
3	TD0001-24			2,4 mm	3/32"	50 mm	10N24	10
3	TD0001-32			3,2 mm	1/8"	50 mm	10N25	10
3	TD0001-40			4,0 mm	5/32"	50 mm	54N20	10
3	TD0001-48			4,8 mm	3/16"	50 mm	30028	10
4	TQ0002						18CG	10
4	TQ0008 *						-	10
7	BW0056					58 mm	57Y03	10
7	BW0066					117 mm	57Y02	10
7	BW0067	I 🖷				22,5 mm	57Y04	10
7	EA0130	0						10

^{*} ONLY FOR 18 HC


GAS LENS

	CODE		Gr	Q)	←→	REF	
1	TC0031		4	6,4 mm	1/4"	42 mm	54N18	10
1	TC0032		5	8 mm	5/16"	42 mm	54N17	10
1	TC0033	 	6	9,8 mm	3/8"	42 mm	54N16	10
1	TC0034		7	11,2 mm	7/16"	42 mm	54N15	10
1	TC0035		8	12,7 mm	1/2"	42 mm	54N14	10
1	TC0036		11	19 mm	3/4"	42 mm	53N87	10
1	TC0037			17,2 mm		28,6 mm	54N19	10
1	TC0086		5	8 mm	5/16"	76 mm	54N17L	10
1	TC0087		6	9,5 mm	3/8"	76 mm	54N16L	10
1	TC0088		7	11 mm		76 mm	54N15L	10
2	TE0006-05			0,5 mm	.020"	50 mm	45V29	10
2	TE0006-10			1,0 mm	.040"	50 mm	45V24	10
2	TE0006-16			1,6 mm	1/16"	50 mm	45V25	10
2	TE0006-20			2,0 mm	5/64"	50 mm	-	10
2	TE0006-24	Cu + CuZn		2,4 mm	3/32"	50 mm	45V26	10
2	TE0006-32			3,2 mm	1/8"	50 mm	45V27	10
2	TE0006-40			4,0 mm	5/32"	50 mm	45V28	10
3	TD0022-10			1,0 mm	.040"	52 mm	-	10
3	TD0022-16			1,6 mm	1/16"	52 mm	-	10
3	TD0022-24			2,4 mm	3/32"	52 mm	-	10
3	TD0022-32			3,2 mm	1/8"	52 mm	-	10
3	TD0022-40			4,0 mm	5/32"	52 mm	-	10
4	TQ0003						54N01	10
7	BW0056					58 mm	57Y03	10
7	BW0066	1				117 mm	57Y02	10
7	BW0067	#				22,5 mm	57Y04	10
7	EA0130	0						10

Protection gas flow is usually guttered by a STANDARD ceramic nozzle (Figure 1). Such flow is affected by turbulences of torch head which are caused by the inlet pressure. In order to assure an uniform gas distribution, above all in stainless steel, titanium and aluminium alloys welding, we suggest the use of GAS LENS spare parts. The electrode holder equipped with a gas lens net, uniforms the flow (Figure 2) and aid to save the protection gas. Where permitted by external dimensions, it is recommended the JUMBO version which increases the protected surface with advantage for welding quality (Figure 3).

GAS LENS XL (JUMBO)

_			_	_	_			_
	CODE		Gr	Q)	\longleftrightarrow	REF	
1	TC0118		8	12,7 mm	1/2"	48 mm	57N74	10
1	TC0119		10	15,7 mm	5/8"	48 mm	53N88	10
1	TC0120		12	19,5 mm	3/4"	48 mm	53N87	10
2	TE0009-16			1,6 mm	1/16"	51 mm	45V16	2
2	TE0009-24			2,4 mm	3/32"	51 mm	45 V 64	2
2	TE0009-32			3,2 mm	1/8"	51 mm	995795	2
2	TE0009-40			4,0 mm	5/32"	51 mm	45V63	2
3	TD0001-05			0,5 mm	.020"	50 mm	10N21	10
3	TD0001-10			1,0 mm	.040"	50 mm	10N22	10
3	TD0001-16			1,6 mm	1/16"	50 mm	10N23	10
3	TD0001-20			2,0 mm	5/64"	50 mm	-	10
3	TD0001-24			2,4 mm	3/32"	50 mm	10N24	10
3	TD0001-32			3,2 mm	1/8"	50 mm	10N25	10
3	TD0001-40			4,0 mm	5/32"	50 mm	54N20	10
3	TD0001-48			4,8 mm	3/16"	50 mm	30028	10
4	TQ0027						54N63	10
7	BW0056					58 mm	57Y03	10
7	BW0066					117 mm	57Y02	10
7	BW0067	41				22,5 mm	57Y04	10
7	EA0130	0						10





TIG 17 / 18 / 18 HC / 26 - STUBBY CONSUMABLES

2




STUBBY

	CODE		Gr	Q	Ď	←→	REF	
1	TC0012		4	6,4 mm	1/4"	30 mm	13N08	10
1	TC0013		5	8 mm	5/16"	30 mm	13N09	10
1	TC0014		6	9,8 mm	3/8"	30 mm	13N10	10
1	TC0015		7	11,2 mm	7/16"	30 mm	13N11	10
1	TC0016		8	12,7 mm	1/2"	30 mm	13N12	10
1	TC0017		10	15,7 mm	5/8"	30 mm	13N13	10
1	TC0096		4	6,5 mm	1/4"	48 mm	796F71	10
1	TC0097		5	8 mm	5/16"	48 mm	796F72	10
1	TC0098		6	9,5 mm	3/8"	48 mm	796F73	10
1	TC0101		4	6,5 mm	1/4"	63 mm	796F75	10
1	TC0102		5	8 mm	5/16"	63 mm	796F76	10
1	TC0103		4	6,5 mm	1/4"	89 mm	796F79	10
2	TE0002-00			1,0 mm	.040"	24,5 mm	17CB20	10
3	TD0002-10			1,0 mm	.040"	29 mm	10N22S	10
3	TD0002-16			1,6 mm	1/16"	29 mm	10N23S	10
3	TD0002-20			2,0 mm		29 mm		10
3	TD0002-24			2,4 mm	3/32"	29 mm	10N24S	10
3	TD0002-32			3,2 mm	1/8"	29 mm	10N25S	10
4	TQ0002						18CG	10
4	TQ0008 *						-	10
7	BW0056	14				58 mm	57Y03	10
7	BW0066	 				117 mm	57Y02	10
7	BW0067	149				22,5 mm	57Y04	10
7	EA0130	0						10

1

The Stubby collets allow the use of the small nozzles of the 9/20 series on the 17/18/26 torch bodies.



STUBBY GAS LENS

3

CODE		Gr	Q	Ď	←	REF	
TC0041		4	6,4 mm	1/4"	25,5 mm	53N58	10
TC0042		5	8 mm	5/16"	25,5 mm	53N59	10
TC0043		6	9,8 mm	3/8"	25,5 mm	53N60	10
TC0044		7	11,2 mm	7/16"	25,5 mm	53N61	10
TC0045		8	12,7 mm	1/2"	25,5 mm	53N61S	10
TE0095-16			1,6 mm	1/16"	29 mm		10
TE0095-20			2,0 mm	5/64"	29 mm		10
TE0095-24	Cu + CuZn		2,4 mm	3/32"	29 mm	-	10
TE0095-32	Ou + Ouzii		3,2 mm	1/8"	29 mm	-	10
TD0095-16			1,6 mm	1/16"	30,7 mm	-	10
TD0095-20			2,0 mm	5/64"	30,7 mm	-	10
TD0095-24			2,4 mm	3/32"	30,7 mm	-	10
TD0095-32			3,2 mm	1/8"	30,7 mm	-	10
TQ0095	1					18CG20	10
TQ0096 *	•						10
BW0056	14				58 mm	57Y03	10
BW0066					117 mm	57Y02	10
BW0067	I 14				22,5 mm	57Y04	10
EA0130	0						10

7

STUBBY GAS LENS (C u)

	CODE		Gr	Q	<u>)</u>	\longleftrightarrow	REF	
1	TC0041		4	6,4 mm	1/4"	25,5 mm	53N58	10
1	TC0042		5	8 mm	5/16"	25,5 mm	53N59	10
1	TC0043		6	9,8 mm	3/8"	25,5 mm	53N60	10
1	TC0044		7	11,2 mm	7/16"	25,5 mm	53N61	10
1	TC0045		8	12,7 mm	1/2"	25,5 mm	53N61S	10
2	TE0096-16			1,6 mm	1/16"	30,6 mm	-	10
2	TE0096-20			2,0 mm	5/64"	30,6 mm	-	10
2	TE0096-24	Cu		2,4 mm	3/32"	30,6 mm	•	10
2	TE0096-32	Ou		3,2 mm	1/8"	30,6 mm	-	10
3	TD0096-16			1,6 mm	1/16"	33 mm	-	10
3	TD0096-20			2,0 mm	5/64"	33 mm	-	10
3	TD0096-24			2,4 mm	3/32"	33 mm	-	10
3	TD0096-32			3,2 mm	1/8"	33 mm	-	10
4	TQ0095	•					18CG20	10
4	TQ0096 *	•						10
7	BW0056	14				58 mm	57Y03	10
7	BW0066	I -				117 mm	57Y02	10
7	BW0067	=4 <u> </u>				22,5 mm	57Y04	10
7	EA0130	0						10

^{*} ONLY FOR 18 HC

^{*} ONLY FOR 18 HC

^{*} ONLY FOR 18 HC